

LED DRIVER 250/350/500/700mA 10/15/20W

CODE 1836 / SKU 6008020

astro



SPECIFICATION

TYPE	Constant current
DRIVER CURRENT	250 / 350 / 500 / 700mA
DRIVER VOLTAGE	N/A
DIMMABLE	DALI
ELECTRICAL CLASS	CLASS 2
SUPPLY VOLTAGE	110-120V AC 220-240V AC
SUPPLY FREQUENCY	50/60Hz
POWER FACTOR	0.95
MIN. OUTPUT VOLTAGE	2.0V DC
MAX. OUTPUT VOLTAGE	43.0 / 36.0 / 40.0 / 28.0V DC
MIN. OUTPUT POWER	0.5 / 0.7 / 1.0 / 1.4W
MAX. OUTPUT POWER	10.75 / 15.05 / 20.0 / 19.6W
INRUSH CURRENT	5A 50μS
IP RATING	IP20
WORKING TEMPERATURE	-25°C - +50°C
CONNECTION TYPE	Push connection
LENGTH	108mm
WIDTH	52mm
HEIGHT	22mm
MIN. CIRCULAR APERTURE	57mm/2-1/4"
MAX. LED DISTANCE	5m 23 / 20AWG
MANUFACTURER	TCI
MODEL NUMBER	DC MINI JOLLY (@250/350/500/700mA)

Wire LED products in series.

To calculate product compatibility, visit the driver calculator on each product page on the Astro website.

See the Astro website for installation guides.